

Braeburn®


8205

Up to 3 Heat / 2 Cool Heat Pump
Up to 2 Heat / 2 Cool Conventional
Smart Wi-Fi Universal Thermostat



BlueLink
smart connect

Phone not included.



NEW!
Ultra-Slim
Design

Wi Fi

5 YEAR
LIMITED
WARRANTY

Thermostat Features

- 7 Day, 5-2 Day or Non-Programmable
- Large 4.4 sq. in. Backlit Display
- Bright Blue Backlight
- Auto or Manual Changeover
- User and Installer Lock Modes
- SmartLimit® Temperature Limits
- Auxiliary Heat Fossil Fuel Option
- Hardwire or Battery Powered
- Circulating Fan Mode
- Works without common (C) wire on most systems; requires common on Heat Pump, Heat Only or Cool Only Systems

Application Features

- Compatible with Virtually All Smartphones, Tablets or PC's
- Multi-Color Program Groups Simplify Scheduling
- Flexible Vacation and Holiday Scheduling
- Text and E-Mail Service and Temperature Alerts
- BlueLink QuickCopy® Allows User to Duplicate Program and Configuration to Other Thermostats
- QuickEdit® Makes Schedule Changes Easy
- BlueLink SmartData® Energy Report Capability
- Monitor and Control Multiple Thermostats
- Easy Access Dealer Information
- Optional Geofencing for Increased Energy Savings



FREE Contractor Branding
on Removable Face Plate!



Compatible with Amazon Alexa
Amazon Alexa is a trademark of Amazon.com, Inc.

www.braeburnonline.com

works with the
Google Assistant

Toll-Free 866.268.5599 (U.S.) +1.630.844.1968 (Outside the U.S.)

Braeburn®



BlueLink Smart Connect® Application Screens

FREE app to monitor and control multiple thermostats from virtually any Smartphone, Tablet or PC


Multi-Color Program Groups



Vacation and Holiday Scheduling



Geofencing



BlueLink QuickCopy® Feature



BlueLink SmartData® Reports




Service and Temperature Alerts



BlueLink Service Connect® Application Screens

FREE app for contractors, allowing them the ability to monitor and manage multiple customer thermostats



Product Specifications

Dimensions:	4.25" x 5.12" x 1"
Electric Rating:	24 Volt AC (18-30 Volt AC) 1 amp maximum load per terminal 5 amp total maximum load (all terminals)
AC Power:	18-30 Volt AC
DC Power:	3.0 Volts DC (2 "AA" Alkaline batteries included)
Note:	Works without common (C) wire on most systems; requires common on Heat Pump, Heat Only or Cool Only Systems
Compatibility:	Heat pump systems up to 3 heat/2 cool, Conventional systems up to 2 heat/2 cool
Wi-Fi Communication:	802.11 b/g/n 2.4GHZ
Control Range:	45° to 90° F (7° to 32° C)
Display Range:	40° to 99° F (5° to 37° C)
Accuracy:	+/- 1° F (+/- .5° C)
Terminations:	Rh, Rc, W2, W1/E/W3, O/B, G, Y2, Y1, C

Shipping Information

INDIVIDUAL CARTON	MASTER CARTON
Dimensions: 5.0" x 6.0" x 1.7"	Quantity: 3
Weight: 1.0 lbs.	Dimensions: 6.75" x 5.5" x 5.7"
	Cubic Feet: .13
	Weight: 3.25 lbs.

Braeburn 8205 Replaces*

Honeywell® TH8732WF, TH6220WF	Pro1® T855i, T701i, T721i
Emerson® 1F86U-42WF	Nest® T100577, T200577, T3007ES

*Verify specific application requirements. All trademarks are the property of their respective owners.

Accessories

5970	Universal Thermostat Guard
2940	Vertical J-Box Adapter Wall Plate (6.5" x 5.1")
2950	Universal Wall Plate (6.5" x 6.5")

FREE Contractor Branding Available! Visit our website (www.braeburnonline.com) for more information, contact your local distributor or call our sales department toll-free at 866.268.5599 (U.S.), +1.630.844.1968 (Outside the U.S.).

Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Google and Google Play are trademarks of Google LLC. Amazon, Alexa and all related logos are trademarks of Amazon.com, Inc. or its affiliates.